

DIAMANTKAPPSKIVER STANDARD**Venom multilayer****- for betong**

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type		
300	2,8	8,0	20+20	●	●	
350	3,2	8,0	20+20	●	●	
400	3,2	8,0	20+20	●	●	
415	3,2	8,0	20+20	●	●	
425	3,2	8,0	20+20	●	●	
450	3,2	8,0	20+20	●	●	
500	3,8	8,0	20+20	●	●	●
600	4,5	8,0	20+20	●	●	●
650	4,5	8,0	20+20	●	●	●
700	4,5	8,0	20+20	●	●	●
800	4,5	8,0	20+20	●	●	●
900	4,5	8,0	20+20	●	●	●
1000	4,5	8,0	20+20	●	●	●
1200	4,5	8,0	20+20	●	●	●
1500	4,5	8,0	20+20	●	●	●
1600	4,5	8,0	20+20	●	●	●

TYPE	FARGE	BRUKSOMRÅDE
VENOM E	●	Hard betong • Handsag • Små maskiner
VENOM A	●	Normal betong • Handsag
VENOM C	●	Hard betong • Normal betong • Veggsag
VENOM B	●	Normal betong • Veggsag • Gulvsag
VENOM D	●	Normal betong • Dårlig betong • Gulvsag











“NÅR DET GJELDER DIAMANTVERKTØY OG MASKINER FOR ARMERT BETONG”

SCAN-DIAMANT AS

Sollihagaen 19 • N-7374 Røros • Tlf 72 41 27 02 • Fax 72 41 01 35 • Mobil 917 39 665
Etter kontortid 72 41 28 33 • E-post: post@scandiamant.no • www.scandiamant.no















DIAMANTKAPPSKIVER TYNNVEGGEDE**Venom multilayer**

- for betong

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type
600	3,8	8,0	20	 
700	3,8	8,0	20	 
800	3,8	8,0	20	 
800	4,1	8,0	20	 

DIAMANTKAPPSKIVER**FORSAGINGSBLAD****Venom multilayer**

- for betong

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type
400	3,5	8,0	20+20	 
600	5,0	8,0	20+20	  
700	5,0	8,0	20+20	  
800	5,0	8,0	20+20	  
900	5,0	8,0	20+20	  



“NÅR DET GJELDER DIAMANTVERKTØY OG MASKINER FOR ARMERT BETONG”

 **SCAN-DIAMANT AS**

Sollihagaen 19 • N-7374 Røros • Tlf 72 41 27 02 • Fax 72 41 01 35 • Mobil 917 39 665
Etter kontortid 72 41 28 33 • E-post: post@scandiamant.no • www.scandiamant.no

DIAMANTKAPPSKIVER

- for granitt

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type
300	3,2	11,0	20+20	GWT 5 M – GWT 7 M
350	3,2	11,0	20+20	GWT 5 M – GWT 7 M
400	3,5	11,0	20+20	GWT 5 M – GWT 7 M
450	3,8	11,0	20+20	GWT 5 M – GWT 7 M
500	3,8	11,0	20+20	GWT 5 M – GWT 7 M
600	4,5	11,0	20+20	GWT 5 M – GWT 7 M
700	4,5	11,0	20+20	GWT 5 M – GWT 7 M
800	4,5	11,0	20+20	GWT 5 M – GWT 7 M

*Mot et pristillegg kan kappskivene leveres lydempet.

GWT 5 M: Myk og normal stentype. Større maskiner.

GWT 7 M: Harde stentyper. Mindre maskiner.

DIAMANTKAPPSKIVER

- for asfalt

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type
250	3,0	6,0	40	AS ●
300	3,2	6,0	40	AS ●
350	3,2	6,0	40	AS ●
400	3,5	6,0	40	AS ●
450	3,8	6,0	40	AS ●
500	3,8	6,0	40	AS ●
600	4,5	6,0	40	AS ●
700	4,5	6,0	40	AS ●
800	4,5	6,0	40	AS ●

* Alle dimensjoner leveres med støttesegment.

NB: Husk å oppgi diameter på senterhull**DIAMANTKAPPSKIVER STANDARD**

"NÅR DET GJELDER DIAMANTVERKTØY OG MASKINER FOR ARMERT BETONG"

SCAN-DIAMANT AS

 Sollihagaen 19 • N-7374 Røros • Tlf 72 41 27 02 • Fax 72 41 01 35 • Mobil 917 39 665
 Etter kontortid 72 41 28 33 • E-post: post@scandiamant.no • www.scandiamant.no

- for betong

Diameter	Segment- tykkelse	Segment- høyde	Segment- lengde	Type
300	2,8	8,0	20+20	● ● ●
350	3,2	8,0	20+20	● ● ●
400	3,2	8,0	20+20	● ● ●
425	3,2	8,0	20+20	● ● ●
450	3,2	8,0	20+20	● ● ●
500	3,8	8,0	20+20	● ● ●
600	4,5	8,0	20+20	● ● ●
650	4,5	8,0	20+20	● ● ●
700	4,5	8,0	20+20	● ● ●
800	4,5	8,0	20+20	● ● ●
900	4,5	8,0	20+20	● ● ●
1000	4,5	8,0	20+20	● ● ●
1200	4,5	8,0	20+20	● ● ●
1500	4,5	8,0	20+20	● ● ●
1600	4,5	8,0	20+20	● ● ●

TYPE	FARGE	BRUKSOMRÅDE
CW 47	●	Ekstra hard betong • Mye armering • Veggsag • Handsag
CW 70	●	Normal betong • Veggsag • Gulvsag
CW 80	●	Dårlig betong • Store maskiner • Gulvsag
AS	●	Asfalt • Tegl • Leca

DIAMANTKAPPSKIVER TYNNVEGGEDE



“NÅR DET GJELDER DIAMANTVERKTØY OG MASKINER FOR ARMERT BETONG”

SCAN-DIAMANT AS

Sollihagaen 19 • N-7374 Røros • Tlf 72 41 27 02 • Fax 72 41 01 35 • Mobil 917 39 665
Etter kontortid 72 41 28 33 • E-post: post@scandiamant.no • www.scandiamant.no

- for betong

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type		
600	3,8	8,0	20	●	●	●
700	3,8	8,0	20	●	●	●
800	3,8	8,0	20	●	●	●
800	4,1	8,0	20	●	●	●

DIAMANTKAPPSKIVER

FORSAGINGSBLAD

- for betong

Diameter	Segment-tykkelse	Segment-høyde	Segment-lengde	Type		
400	3,5	8,0	20+20	●	●	●
600	5,0	8,0	20+20	●	●	●
700	5,0	8,0	20+20	●	●	●
800	5,0	8,0	20+20	●	●	●
900	5,0	8,0	20+20	●	●	●



“NÅR DET GJELDER DIAMANTVERKTØY OG MASKINER FOR ARMERT BETONG”

SCAN-DIAMANT AS

Sollihagaen 19 • N-7374 Røros • Tlf 72 41 27 02 • Fax 72 41 01 35 • Mobil 917 39 665
Etter kontortid 72 41 28 33 • E-post: post@scandiamant.no • www.scandiamant.no